

Pro XD Full-Size Gas



Key Specifications

Gas	1,850	200-Hr
Fuel Type	Ibs Payload	Maintenance Interval

ANSI/OPEI Certification

Polaris Industries Inc. certifies that these vehicles complies with the American National Standard for Multipurpose off-Highway Utility Vehicles, ANSI/OPEI B71.9 – 2016 Standard

Engine & Drivetrain

Air Intake	Front Air Intake with Donaldson® Cyclonic Air Filter
Cooling	Liquid
Cylinders Displacement	1,000 cc
Drive System Type	On-Demand 4x4
Engine Type	ProStar 1,000 cc Gas
Fuel System/Battery	Electronic Fuel Injection
Horsepower	39.5 HP
Maintenance Interval	200 Hours (50 Hour initial)
Top Speed	Adjustable up to 40 mph (64 km/h)
Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft

Dimensions

Bed Box Dimensions (L x W x H)	43.5 x 54 x 11.5 in (110.5 x 137 x 29 cm)
Box Capacity	1,250 lb (567 kg)
Estimated Dry Weight	1,568 lb (711 kg)
Fuel Capacity	11.5 gal (43.5 L)
Ground Clearance	11 in (27.9 cm)
GAWR	3,600 lb (1,632 kg)

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising.

Manage Settings

Accept

Decline All

Person Capacity	2
Turning Radius	144 in (365 cm)
Wheelbase	85 in (215.9 cm)

Brakes

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
Parking Brake	Park In-Transmission

Additional Specifications

Adjustable Driver Seat	Not Equipped
Cargo System	Lock & Ride®
Hitch Type	Standard 2 in (5 cm) Receiver
Instrumentation	All Digital Gauge, Speedometer, Odometer, Tachometer, 2 Tripmeters, Hour Meter, Gear Indicator, Diff Lock Indicator, Hi-Temp Light, Clock, Clutch Belt Slip Warning, Glow Plug Indicator, Low Oil Pressure Indicator, Seat Belt Indicator
Lighting	55W low/ 60W high, LED Tail
Other Standard Features	Horn, Backup Alarm, Password protected, electronically adjustable speed limiting
Seat Covering	Kevlar®-Backed Vinyl (Grey)
Tilt Steering	Standard

Tires / Wheels

Electronic Power Steering	Optional
Front Tires	26 x 10-12 Duro® DI-2042 Power Grip (M/T)
Hubs	Front: Steel; Rear: Ductile Iron
Rear Tires	26 x 10-12 Duro® DI-2042 Power Grip (M/T)
Wheels	12 x 6 HD Steel - Gloss Black

Suspension

Front Suspension	9 in (22.9 cm)
Rear Suspension	9 in (22.9 cm)

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising.